

# rsync daemon service on OpenIndiana



As of December 2011, OpenIndiana still does not include a service manifest for running an `rsync` daemon out of the box. Until this changes, others may find the following service manifest and method files helpful.

This has been tested in OpenIndiana 151a.

## Install and configure the SMF service for rsync and the daemon itself

Before starting with this guide, make sure that `rsync` software is installed on the machine. It is not installed per default in local zones, but can be done so with `pkg`:

```
pkg install network/rsync
```

## Prepare files for SMF services configuration

To see all attachments described in this page, click on the small paper clip icon at the top left.

Add SMF manifest and method scripts, and initial configuration for `rsync` itself (as `root`):

- copy (or `wget`) the attached file "`rsyncd.xml`" to: `/var/svc/manifest/network/rsyncd.xml`
- copy (or `wget`) the attached file "`rsyncd`" to: `/lib/svc/method/rsyncd`
- set the execute permission on the above file for user `root`:

```
chmod u+x /lib/svc/method/rsyncd
```

(Thanks to <http://robbiecrash.me/?p=22> for pointing out that I missed the above `chmod` step)

- copy (or `wget`) the attached file "`rsync`" to: `/etc/default/rsync`  
NOTE that the variable `RSYNC_ENABLE` is already set to true in this file.
- now create a valid `/etc/rsyncd.conf` file. This must be done or the service will not run.  
For a full list of options see: `man rsyncd.conf`

For an example see this trivial `/etc/rsyncd.conf` file:

```
use chroot = yes
read only = yes
log file = /var/adm/rsyncd_upload.log
log format = - %a - %f
transfer logging = yes

#module to share ISO files
[ISO]
path = /lift/data/ISO
comment = public ISO repository
```

## Import the SMF service manifest

Now you can import the SMF service manifest with the following code:

```
svccfg -v import /var/svc/manifest/network/rsyncd.xml
```

Next check to see the status of the `rsyncd` service – it should be defined but may be not running yet:

```
svcs -a | grep rsyncd
```

...you should see something like this:

```
offline          2:04:55 svc:/network/rsyncd:default
```

## Enable the SMF service

Now you need to enable the service:

```
svcadm enable network/rsyncd
```

### Test that the service is enabled and the daemon actually runs

Now execute the `svcs` command again and also execute `ps`:

```
svcs -a | grep rsync
```

The service should be listed as online now:

```
online          May_16   svc:/network/rsyncd:default
```

Now execute:

```
ps aux | grep rsync
```

you should see something like this

```
root      13351  0.0  0.0 2688 1340 ?        S 02:04:55  0:00 /usr/bin/rsync --d
```

### Test from a client

Note – if you add new modules to `/etc/rsyncd.conf` you **should not** have to restart the `rsyncd` service, as the file is read each time an `rsync` client connects.

Congrats, your `rsyncd` should be working now. Test it out from a client machine using a small file for testing with something like:

```
rsync servername::ISO/some_file.iso /localpath/here/
```

or just get a list of the files and/or directories by using verbose mode and piping to `less`:

```
rsync -v servername::ISO | less
```

Consult the log file referenced in your `rsyncd.conf` file to see info on file transfers. (In this example `/var/adm/rsyncd_upload.log`).

Thanks to [Marcelo Leal](#) for the `rsyncd` [method file](#) (changed here to point to `/usr/bin/rsync`) and also for parts of the service manifest.

### Optional – add automatic ZFS snapshots after rsync uploads

You might want to create ZFS snapshots linked to your incoming `rsync` upload jobs – for example, after a machine backing up to your OpenIndiana server disconnects its rsyncing session. Tricks like this can be done by defining a `post-xfer-exec` hook pointing to a script which handles the logic, in this case [rsync-zfshot.sh](#).

Expanding on a trivial example above, here is another one:

```

use chroot = yes
read only = yes
log file = /var/adm/rsyncd_upload.log
log format = - %a - %f
transfer logging = yes
pid file = /var/run/rsyncd.pid
lock file = /var/run/rsyncd.lock

#module to share ISO files
[ISO]
path = /lift/data/ISO
comment = public ISO repository

#Module available only to a multihomed host which backs up into this path
#and chowns the files to specified UID:GID and sets FS access rights
#(source is a Windows machine with separate user namespace); it is also
#recommended that each backed-up host has a dedicated backup ZFS dataset.
#When a backup attempt is complete, a ZFS snapshot is created, so we can
#walk back to any given complete backup image (i.e. via .zfs/snapshots
#directory with Samba/kCIFS sharing, or via MS Shadow Volumes with kCIFS)
[backup-jamais]
  path = /export/DUMP/windows/JAM AIS
  read only = no
  auth users = backup-jamais
  charset = UTF-8
  ### NOTE: cwRsync clients might require "--iconv=cp1251" on their command
  ###       line to properly upload russian-named files from Windows
  uid = backup-jamais
  gid = backup-jamais
  incoming chmod = Dug=rwX,o-rwx,Fug=rw,o-rwx
  hosts allow = 192.168.1.101/32 123.45.68.101/32
  post-xfer exec = /root/rsync-zfshot.sh -w -v -l -ok

```

The main trickery for this particular quest is in the [rsync-zfshot.sh](#) script attached to this post. It has a number of command-line options to control logging and verbosity, as well as to enable actual snapshotting (dry-runs by default), and perhaps only when the rsync upload was successful (without an rsync error status set). Hopefully, the code and comments (and command-line help) are its best documentation.

- copy (or `wget`) the attached file "[rsync-zfshot.sh](#)" to: `/root/rsync-zfshot.sh` or any other location referenced in your config file module above
- set the execute permission on the above file for user `root`:

```
chmod u+x /root/rsync-zfshot.sh
```

- You might be required to also delegate the ZFS snapshotting access rights to the backup user (but test first to see if this is really needed):

```
zfs allow -l -d -u backup-jamais snapshot,rename,mount \
  rpool/export/DUMP/windows/JAM AIS
```

NOTE: the `-l -d` options set this permission locally on the named dataset and on its descendants, including those created in the future.